425H | 655W | 655D (mm) Standard weight: 53kg



# **KEY FEATURES**

- One-piece design cannot be disassembled or weaponised
- → 100% waterproof construction with hygienic wipe-clean surface
- Water resistant, UV stabilised material makes items suitable for outdoor use
- → Reduced-ligature design features
- → Safely rounded corners
- → Polyethylene material is 100% recyclable
- → Strength and durability tested for severe contract use, (inc. 500kg static load test)













## MATERIAL/FABRICATION

Rotationally moulded, durable polyethylene, one-piece construction provides excellent strength and stability. Flamed, textured finish further strengthens the fire-retardant, water-resistant, UV-stabilised shell. Anti-microbial material gives high chemical resistance (e.g. ammonia, sodium hydroxide) throughout the product.

## TEST STANDARDS

- → Tested to ANSI/BIFMA X5:5:2012 standards
- → Fire retardant to CAL 133 and UL 94 HB
- → Fire retardant to BS 5852:2006 ignition source 5, CAL 133, UL 94 HB and DIN 66084
- → UV resistance tested to UV 21+ stating it can withstand 21,000 sunlight hours
- → Static load tested to a weight of 500kg
- → Antibacterial Activity MOD iso 11196:2011
- → Ryno ISO 11925 (2020)

## **OPTIONS**

- → Unweighted at 9kg Standard weighting (53kg) or additionally weighted
- → Heavy-duty anchor bracket for floor fixing
- → Connecting plates to link tables together
- → Lime Green (LG) and Vegas Yellow (VY) colours have a minimum order quantity of 12 units

## **COLOUR/FINISH**





## **DELIVERY**

[core colours] leadtime 5 weeks | [non-core colours] will have longer leadtimes and additional costs

# **ASSEMBLY**

Arrives assembled and ready to use

## INSTALLATION/FITTING

Please advise if floor fixing is required when ordering as fixed items are made differently. All products must be fitted carefully following Pineapple's product instructions (where available). If not, any guarantee is at risk of becoming null and void

## **MAINTENANCE**

Avoid using abrasive materials or cleaning agents, solvents, steam cleaning or jet washing. Use bleach and chlorine disinfectant with caution and avoid placing in close proximity to sources of heat. Read more on our website.

#### WARRANTY

Lifetime guarantee against all manufacturing faults

#### DISCLAIMER

Extreme temperature changes (e.g. a cold night followed by a warm sunny day) may cause air inside the product to expand, causing short-term changes to its shape

Due to the nature of the rotational moulding process, flat surfaces on Ryno® products may feature slight undulations which do not detract from the product's strength or durability.