RYNO® OPEN WARDROBE



UK Registered Design No. 6195591 / 6195592











KEY FEATURES

- One-piece design makes products water-resistant and prevents concealment of contraband
- → Reduced-ligature design features
- Floor and wall securable with security fixings
- → Sloping shelves reduce ability to climb
- → Polyethylene material is 100% recyclable
- → 100% waterproof construction with hygienic wipe-clean surface

MATERIAL/FABRICATION

Rotationally moulded, durable polyethylene, one-piece construction provides excellent strength and stability. Flamed, textured finish further strengthens the fire-retardant, water-resistant, UV-stabilised shell. Anti-microbial material gives high chemical resistance (e.g. ammonia, sodium hydroxide) throughout the product. Item is fully recyclable as polyethylene can be melted down to create a whole new product.

Our Ryno Open Wardrobe has been designed to be the same depth and width as Ryno Chest and Ryno Desk.

TEST STANDARDS

- → Tested to ANSI/BIFMA X5:5:2012 standards
- → Fire retardant to BS 5852:2006 ignition source 5, CAL 133, UL 94 HB and DIN 66084
- → Tested to BS EN 16121:2013+A1:2017 Test Level 2 Severe
- → UV resistance tested to UV 21+ stating it can withstand 21,000 sunlight hours
- → Antibacterial Activity MOD iso 11196:2011
- → Ryno ISO 11925 (2020)

COLOUR/FINISH


CORE COLOURS	Moonwalk Grey	Dusty Blue	Cool Green
2	Granite	Epic Blue	Icon Purple
NON-50RE COLOURS	Thunder Grey	Dusty Pink	OceanGreen
	Sand	Teal	
	Warm Terracotta	Violet Purple	
	Lime Green	Vegas Yellow	hese colours have a minimum order quantity of 12 units

OPTIONS

 2 options available (clothes hanging space or fully shelved)

Ryno Open Wardrobe (fully shelved) 1RYOW-00 2000H | 698W | 510D (mm) Weight: 45kg





RYNO® OPEN WARDROBE

DELIVERY

[core colours] leadtime 5 weeks | [non-core colours] will have longer leadtimes and additional costs

ASSEMBLY

Arrives assembled and ready to use. All products must be secured to the wall and not be freestanding to avoid risk of injury

INSTALLATION/FITTING

Please contact us for installation instructions. Products must also be wall fixed (by the customer, using wall anchors and fixings of their choice) for additional strength

MAINTENANCE

Avoid using abrasive materials or cleaning agents, solvents, steam cleaning or jet washing. Use bleach and chlorine disinfectant with caution and avoid placing in close proximity to sources of heat. Read more on our website.

WARRANTY

Lifetime guarantee against all manufacturing faults

DISCLAIMER

Extreme temperature changes (e.g. a cold night followed by a warm sunny day) may cause air inside the product to expand, causing short-term changes to its shape

Due to the nature of the rotational moulding process, flat surfaces on Ryno® products may feature slight undulations which do not detract from the product's strength or durability.