1RYO-00 838H | 450W | 450D (mm) Weight: 10.5kg

Capacity: 25 litres



KEY FEATURES

- → Sloping design features and the inside of the opening
- → Securely locked by staff to prevent unauthorised access
- → 25 litre internal washable bin avoids the safety risks normally associated with liner bags
- → Narrow opening reduced spillages in the event of overturning
- → 100% waterproof construction with hygienic wipe-clean surface
- → Polyethylene material is 100% recyclable
- → Base made from 100% recycled content
- → Recommended for supervised areas











MATERIAL/FABRICATION

Rotationally moulded, durable polyethylene, one-piece construction provides excellent strength and stability. Flamed, textured finish further strengthens the fire-retardant, water-resistant shell. Hygienic wipe-clean surface, quick to dry ready to be used again. For security, you can choose between an innovative hidden floor fixing system or optional weighting to prevent the SafeWaste unit from being picked up or moved.

The rigid internal liner replaces typical liner bags, reducing safety risks associated with them. This item is fully recyclable as polyethylene can be melted down to create a whole new product.

TEST STANDARDS

- → Tested to ANSI/BIFMA X5:5:2012 standards
- → Fire retardant to CAL 133 and UL 94 HB

OPTIONS

- -> Available as a floor fixed option
- → Heavyweight option (51kg) 1RYQ-51
- → Optionally made with 40% reused content

COLOUR / FINISH



RYNO® SAFEWASTE REDUCED-LIGATURE BIN

DELIVERY

[core colours] leadtime 5 weeks | [non-core colours] will have longer leadtimes and additional costs

ASSEMBLY

Arrives assembled and ready to use

INSTALLATION/FITTING

Additional weighting can be carried out prior to delivery. Please advise if floor fixing is required when ordering as fixed items are made differently. All products must be fitted carefully following Pineapple's product instructions (where available). If not, any guarantee is at risk of becoming null and void

Floor fixing is advisable for challenging environments - please specify at order stage if a floor-fixing kit is required.

MAINTENANCE

Avoid using abrasive materials or cleaning agents, solvents, steam cleaning or jet washing. Use bleach and chlorine disinfectant with caution and avoid placing in close proximity to sources of heat. Read more on our website.

WARRANTY

Lifetime guarantee against all manufacturing faults

DISCLAIMER

Extreme temperature changes (e.g. a cold night followed by a warm sunny day) may cause air inside the product to expand, causing short-term changes to its shape

Due to the nature of the rotational moulding process, flat surfaces on Ryno® products may feature slight undulations