





Pineapple

Developed in association with Stephen N. Parker, AIA NCARB LEED AP (Mental + Behavioural Health Design Leader)



KEY FEATURES

- Smooth, petal-shaped forms inspired by nature and biophilic design
- Modular design that supports grounding and calming spaces
- Heavily weighted to 39kg as standard to deter misuse (other weight options available)
- Integrated water run-off prevents pooling
- Hygienic wipe-clean material
- Water-resistant material which is 100% recyclable
- UV stabilised material suitable for outdoor use
- Organic form and sensory ripple detail designed to soften the built environment
- Strength and stability tested for severe contract use

MATERIAL/FABRICATION

The **Ryno® Blossom Bench** was developed in association with Stephen N. Parker, AIA, NCARB, LEED AP, Mental + Behavioural Health Design Leader, for challenging environments, combining a distinctive organic form with robust construction. Its smooth, petal-shaped profile and subtle sensory ripple detailing draw on biophilic design principles, helping to soften institutional spaces and create a calmer, nature-inspired aesthetic.

The bench is manufactured from rotationally moulded, low-density polyethylene (LDPE), creating a strong, seamless construction with no exposed joins or seams. The water-resistant, hygienic surface is easy to wipe clean and suitable for demanding environments.

The non-porous polyethylene contains no organic matter that could provide a food source for bacteria or bedbugs, helping to support hygiene and infection control. The UV stabilised material is also fully recyclable and suitable for both indoor and outdoor use, with integrated water run-off helping to prevent water pooling.

Heavily weighted to approximately 39kg as standard, the Blossom Bench is designed to deter misuse and provide greater stability, with a concealed floor-fixing solution also available. Its modular form allows multiple benches to be arranged into flexible, organic seating configurations that support grounding and calming spaces.

TEST STANDARDS

- Fire retardant to BS 5852:2006 ignition source 5, CAL 133, UL 94 HB and DIN 66084:2021-02, DIN 4102
- Tested to ANSI/BIFMA X5.5:2012 standard
- NFPA 261 (class 1) Standard Method of Test
- Antibacterial Activity MOD ISO 22196:2011
- Ryno ISO 11925 (2020)
- Seat static load tested to 750kg - testing conducted by Pineapple

COLOUR/FINISH

	Granite		Icon Purple		Moonwalk Grey
	Cool Green		Epic Blue		
	Sand		Teal		Violet Purple
	Dusty Blue		Dusty Pink		OceanGreen
	Warm Terracotta		Thunder Grey		
	Lime Green		Vegas Yellow		

these colours have a minimum order quantity of 12 units

CORE COLOURS

NON-CORE COLOURS

T

+44 (0)1622 237830

E

sales@pineapplecontracts.com

W

uk.pineapplecontracts.com

Pineapple

OPTIONS

- Hidden hard floor fixing solution (32kg) - 1RYBN-F-00
- Unweighted model (39kg) - 1RYBN-00
- Weighted model (127kg) - 1RYBN-127

DELIVERY

[core colours] leadtime 8 weeks | [non-core colours] will have longer leadtimes and additional costs.

ASSEMBLY

Arrives assembled and ready to use .

INSTALLATION/FITTING

Additional weighting can be added prior to delivery where required. A blanking plate is supplied as standard with both weighted and unweighted options. The blanking plate is not required where the product is floor fixed.

All products must be installed carefully and in accordance with Pineapple's product installation instructions, where provided. Failure to follow the recommended installation guidance may invalidate the product warranty.

MAINTENANCE

Do not use abrasive materials, harsh cleaning agents, solvents, steam cleaners, or pressure washers. Bleach and chlorine-based disinfectants should be used with caution. Keep the product away from direct heat sources. For full care guidance, visit: <https://uk.pineapplecontracts.com/upholstery/care-guidance/>

WARRANTY

Lifetime guarantee against all manufacturing faults.

DISCLAIMER

Extreme temperature changes (e.g. a cold night followed by a warm sunny day) may cause air inside the product to expand, causing short-term changes to its shape.

Due to the nature of the rotational moulding process, flat surfaces on Ryno® products may feature slight undulations which do not detract from the product's strength or durability.